



VHF MARINE TRANSCEIVER

IC-M90

Commercial Grade Marine & Land Mobile Radio



Submersible
1m depth for 30 minutes

Tough and submersible for heavy-duty use

The IC-M90 is a submersible (IPX7*), reliable, commercial grade radio. It's simple, yet rugged construction has a polycarbonate casing with an insert-type battery to prevent water intrusion.

* Equivalent to IPX7 of the corresponding International Standard IEC 60529 (2001). 1m depth for 30 minutes.

Long wear printed buttons

Clearly labeled large buttons and positive button action allows for operation in all conditions, even when wearing heavy gloves. The transparent buttons are printed from behind (not on top), so the operating label on the keypad will never be erased under hard use over many years.

Wide LCD allows wide viewing angles

A wide viewing angle, high intensity LCD is used in the IC-M90, offering bright, easy to read characters. The LCD's contrast and backlight are adjustable in 4-levels*. The bright LED indicator on top of the front panel shows the operating status clearly.

* Backlight includes OFF setting.

100 programmable channels for land mobile use

The IC-M90 is suitable for both marine and land mobile applications. Up to 100 programmable channels are available for land mobile use (146-174MHz)*. Each channel is programmable with CTCSS and DTCS tone signaling and wide/narrow channel bandwidth.

* Appropriate license will be required. Ask your dealer for details.

Built-in Voice scrambler

Built-in 32 code voice scrambler provides privacy in secret conversation. The scrambler system is compatible with the UT-112.

Optional VOX (Voice Operated Transmit) headset

With one of Icom's optional headsets* and the OPC-1392, the IC-M90 offers hands-free operation. * See Options listed on back.

Submersible speaker microphone, HM-125*

* Optional, equivalent to IPX7.
(1m depth for 30 minutes)

Icom Inc.

Additional features

- Auto WX scan and WX Alert function
- Instant access to Ch. 16 and Ch. 9 (or call channel)
- Simple add/delete TAG scanning operation
- Monitor button and squelch shift function
- Automatic scan function
- 2 step power saver
- Battery indicator shows remaining battery power in 4 levels
- Beep sound is programmable for each button

SPECIFICATIONS

GENERAL	
• Frequency range	: Marine Tx 156.025-157.425MHz Rx 156.050-163.275MHz LMR Tx/Rx 146.000-174.000MHz
• Usable channels*	: USA, INT, CAN, WX channels; 100 programmable channels
• Channel spacing :	: Marine 25kHz LMR 25/12.5kHz
• PLL channel step (LMR)	: 5/6.25/7.5kHz
• Current drain (at 7.5V DC) :	: Tx 5W output 1.6A typical Rx AF max. 200mA typical
• Operating temperature range :	: Marine -20°C to +60°C; -4°F to +140°F LMR -30°C to +60°C; -22°F to +140°F
• Antenna impedance	: 50Ω (SMA)
• Dimensions (W×H×D)	: 65×145×44 mm; (projections not included) 2 ⁹ / ₁₆ ×5 ²³ / ₃₂ ×1 ²³ / ₃₂ in
• Weight (approx.)	: 410g; 14.5oz (with BP-225)

TRANSMITTER	
• Output power (Hi/Mid/Low)	: 5/3/1W
• Max. frequency deviation :	: Marine ± 5.0kHz LMR (W/N) ± 5.0/2.5kHz
• Frequency error	: ± 5.0ppm
• Spurious emissions	: -70dBc typical
• Adjacent channel power :	: Marine 70dB LMR (Wide/Narrow) 70/60dB
• Hum and noise ratio :	: Marine 40dB LMR (Wide/Narrow) 40/34dB
• Audio harmonic distortion	: Less than 10% (at 60% mod.)

RECEIVER	
• Sensitivity	: 0.25μV typical (12dB SINAD)
• Squelch sensitivity	: 0.35μV typical (at threshold)
• Adjacent channel selectivity :	: Marine 70dB typical LMR (Wide/Narrow) 70/60dB typical
• Spurious response	: 70dB typical
• Intermodulation rejection	: 70dB typical
• Hum and noise ratio :	: Marine 40dB LMR (Wide/Narrow) 40/34dB
• Audio output power	: 0.35W typical (at 10% distortion with an 8Ω load)

Measurement made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.

Supplied accessories: (Depending on version)		
Li-Ion battery versions		
• BP-241	• BC-162	• BC-145
• MB-103	• Antenna	• Hand strap
Ni-Cd battery versions		
• BP-225	• BC-158	• BC-147
• MB-103	• Antenna	• Hand strap

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

BP-223 BATTERY CASE
Battery case for AA (LR6)×6 alkaline cells.

BP-224 7.2V/750mAh Ni-Cd BATTERY PACK
BP-225 7.2V/1100mAh Ni-Cd BATTERY PACK
BP-241 7.4V/1150mAh Li-Ion BATTERY PACK
Provides 7, 10, 11 hours operating time* respectively (approx. at 5 Watts).
* Tx (Hi): Rx: standby=5:5:90

BC-162 DESKTOP CHARGER
+ **BC-145A/E/V AC ADAPTER**
Rapidly charges the BP-224, BP-225 and BP-241 in 1, 1.5, 2 hours, respectively.

BC-158 DESKTOP CHARGER
+ **BC-147A AC ADAPTER**
Regularly charges the BP-225 in 12-18 hours. Cannot charge BP-241.

BC-119N DESKTOP CHARGER
+ **AD-109 CHARGER ADAPTER**
+ **BC-145A AC ADAPTER**
For rapid charging of battery pack. Charges the BP-225 2.2-2.8 hours. Cannot charge BP-241.

CP-17L CIGARETTE LIGHTER CABLE
OPC-515L DC POWER CABLE
For use with the BC-119N or BC-158 with an external DC power supply. (12-16 V DC required)

BC-121N MULTI-CHARGER
+ **AD-109 CHARGER ADAPTER**
+ **BC-124 AC ADAPTER**
For rapid charging of up to 6 battery packs (Six AD-109s are required). Charges the BP-225 2.2-2.8 hours. Cannot charge BP-241.

OPC-656 DC POWER CABLE
For use with the BC-121N with a DC power supply. (12-16V DC required)

MB-86 SWIVEL BELT CLIP
MB-103 BELT CLIP : Alligator type.

HM-125 SPEAKER-MICROPHONE
Full sized, submersible construction corresponds to IPX7 (1 m depth /30 min.).

HS-94 EARPHONE-HEAD HEADSET
HS-95 BEHIND-THE-HEAD HEADSET
HS-97 THROAT MICROPHONE
+ **OPC-1392 HEADSET ADAPTER CABLE**
For VOX hands-free operation. These headsets are not waterproof.



Icom Inc.

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone : +1 (425) 454-8155
Fax : +1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : <http://www.icomamerica.com>

Icom New Zealand

146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone : +64 (09) 274 4062
Fax : +64 (09) 274 4708
E-mail : inquiries@icom.co.nz
URL : <http://www.icom.co.nz>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay,
Kent, CT6 8LD, U.K.
Phone : +44 (0)1227 741741
Fax : +44 (0)1227 741742
E-mail : info@icomuk.co.uk
URL : <http://www.icomuk.co.uk>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone : +886 (02) 2559 1899
Fax : +886 (02) 2559 1874
E-mail : sales@asia-icom.com
URL : <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone : +1 (604) 952-4266
Fax : +1 (604) 952-0900
E-mail : info@icomcanada.com
URL : <http://www.icomcanada.com>

Icom (Europe) Gmbh

Communication Equipment
Himmelgeister Str. 100,
D-40225 Düsseldorf, Germany
Phone : +49 (0211) 346047
Fax : +49 (0211) 333639
E-mail : info@icom-europe.com
URL : <http://www.icomeurope.com>

Icom France Sa

Zac de la Plaine, 1,
Rue Brindejonc des Moulinais BP 5804,
31505 Toulouse Cedex, France
Phone : +33 (5) 61 36 03 03
Fax : +33 (5) 61 36 03 00
E-mail : icom@icom-france.com
URL : <http://www.icom-france.com>

Beijing Icom Ltd.

1305, Wanshang Plaza, Shijingshan Road,
Beijing, China
Phone : +86 (010) 6866 6337
Fax : +86 (010) 6866 3553
E-mail : bjicom@bjicom.com
URL : <http://www.bjicom.com>

Icom (Australia) Pty. Ltd.


A.B.N. 88 006 092 575
290-294 Albert Street, Brunswick,
Victoria, 3056, Australia
Phone : +61 (03) 9387 0666
Fax : +61 (03) 9387 0022
E-mail : sales@icom.net.au
URL : <http://www.icom.net.au>

Icom Spain S.L.

Ctra. de Gracia a Manresa Km. 14,750
08190 Sant Cugat del Valles Barcelona, Spain
Phone : +34 (93) 590 26 70
Fax : +34 (93) 589 04 46
E-mail : icom@icomspain.com
URL : <http://www.icomspain.com>

Icom Polska

Sopot, 3 maja 54, Poland
Phone : +48 (58) 550 7135
Fax : +48 (58) 551 0484
E-mail : icompolska@icompolska.com.pl
URL : <http://www.icompolska.com.pl>



Icom Inc. (Japan), is an ISO 9001 and ISO 14001 certification acquired company.